

UPDATED GATEWAY CORRIDOR DISTRICT LIGHT FIXTURE CUT SHEETS



Revised April 14, 2023

Apr 14, 2023

RE: LaVista Gateway Coridor UCL2
LaVista NE

Type	MFG	Part
S1	Architectural Area Lighting	UCL2-SR-FLR-72L-310-4K7-4W-CL-DBS-SLC-SLA17-AD5-UNV
S1 POLE	Hapco Aluminum Pole Products	RSA20D5-4-P496-ABT-BC
S2	Architectural Area Lighting	UCL2-SR-FLR-72L-310-4K7-4W-CL-DBS-SLC-SLA17-2-AD5-UNV
S2 POLE	Hapco Aluminum Pole Products	RSA20D5-4-P496-ABT-BC



UCL2

ARCHITECTURAL AREA/SITE

DATE: _____ LOCATION: _____
TYPE: _____ PROJECT: _____
CATALOG #: _____

FEATURES

- Reliable, uniform, glare free illumination
- Types 1, 2, 3, 4W, 5Q, and 5W distributions
- 3000K, 4000K, 5000K CCT
- 0-10V dimming ready
- Integral Surge protection: 10k in parallel, 20k in series
- Upgrade Kits
- Utilizes Strike Optics for precise distributions, maximum fixture spacing and minimal backlight.



UNIVERSE®



Universe Large

SPECIFICATIONS

CONSTRUCTION

- All housing components are die cast aluminum 360 alloy, sealed with continuous silicone rubber gaskets
- Standard configurations do not require a flat lens, optional lenses is tempered glass
- All internal and external hardware is stainless steel
- Finish: fade and abrasion resistant, electrostatically applied, thermally cured, triglycidal isocyanurate (TGIC) polyester powdercoat
- Optical bezel finish is match the luminaire housing

LED/OPTICS


- Optical cartridge system consisting of a die cast heat sink, LED engine, TIR optics, gasket and bezel plate
- Optics are held in place without the use of adhesives
- Molded silicone gasket ensures a weather-proof seal around each individual LED.
- Features individual LED optical control based on high performance TIR optical designs
- House Side Shield is available on Standard and Clear Lens options except any Type 5 distribution. House Side Shield is not available for any distribution using a Diffused Lens

INSTALLATION

- Fixtures must be grounded in accordance with national, state and/or local electrical codes. Failure to do so may result in serious personal injury

ELECTRICAL

- Luminaires have integral surge protection, UL recognized and have a surge current rating of 10,000 Amps using the industry standard 8/20uSec wave and surge rating of 372J
- Drivers are UL recognized with an inrush current maximum of <20.0 Amps maximum at 230VAC
- 100%-1% dimming range. Fixture will be wired for low voltage 0-10V dimming control



- Driver and surge suppressor are mounted to a prewired tray with quick disconnects that may be removed from the gear compartment

CONTROLS

- Egress adapter(s) shall slip over a 4"/100mm DIA. pole with the luminaire or arm slipping over the adapter to add a total of 4.5"/114mm to the overall height. Adapter(s) shall be prewired, independently rotatable 359°, and have a cast access cover with an integral lens and lanyard

CONTROLS (CONTINUED)

- Photocell adapter shall include an internal twist lock receptacle. Photocell by others
- Egress adapter shall require an auxiliary 120 volt supply for operation of an integral MR16 lamp in the event of emergency. The lamp may be aimed and locked into position with an adjustment range of 15°-45°. Adapter shall have a socket that accepts miniature bi-pin MR16 lamps up to 50 watts, lamp by others

CERTIFICATIONS

- ETL listed under UL 1598 and CSA C22.2 No. 250.0-08 for wet locations
- This product qualifies as a "designated country construction material" per FAR 52.225-11 Buy American-Construction Materials under Trade Agreements effective 6/06/2020

WARRANTY

- 5 year warranty

KEY DATA	
LUMEN RANGE	4,033–19,516
WATTAGE RANGE	69.9–160.4
EFFICACY RANGE (LPW)	43.3–137.3
INPUT CURRENT RANGE (mA)	335/500/700 mA
WEIGHT	47 lbs 21.3 kg 56 lbs 25.4 kg
EPA	1.05 to 1.95



UCL2

ARCHITECTURAL AREA/SITE

DATE: _____ LOCATION: _____
 TYPE: _____ PROJECT: _____
 CATALOG #: _____

ORDERING GUIDE

Example: UCL2-WND-BLU-FLR-36L-420-4K7-2-CL-BL-WIRSC-SLA2-D-UNV

CATALOG #


HOUSING

UCL2					
Housing	LED Quantity	Lumen Output	CCT/CRI	Distribution	Finish
UCL2 Universe Large 2.0	72L 72 LED	310 450mA Microcore Crossover	AMB Amber-595nm Peak ¹	1 Type I	BLS Black Gloss Smooth
Optional Element		335 335mA, 10000 Lumens	3K7 3000K, 70 CRI	2 Type II	BLT Black Matte Textured
WND Universe Medium with Luminous Window		480 700mA Microcore Crossover	4K7 4000K, 70 CRI	3 Type III	DBS Dark Bronze Gloss Smooth
SR Universe Medium with Luminous Solid Rings		500 500mA, 14000 Lumens	5K7 5000K, 70 CRI	4W Type IV Wide	DBT Dark Bronze Matte Textured
VSL Universe Medium with Luminous Vertical Slots		700 700mA, 19000 Lumens		5Q Type V Square	GTT Graphite Matte Textured
LUM Universe Medium with Luminous Rings				5W Type V Wide	LGS Light Grey Gloss Smooth
Optional Internal Lens					LGT Light Grey Matte Textured
BLU Blue					PSS Platinum Silver Gloss Smooth
RD Red					VGT Verde Green Matte Textured
GRN Green					WHS White Gloss Smooth
Hood Style					WHT White Matte Textured
ANG Angled Hood					Color Option
BEL Bell Hood					CC ³ Custom Color
FLR Flared Hood					
SKB Skirted Bell Hood					

Mounting	Optional Lens	Options	Mounting Options	Voltage
Pole Mount	CL Clear Lens	HS House Side Shield ⁴	PCA-C Photocontrol Adaptor Contemporary	UNV 120-277V
SLA2-D SLA18	DL Diffused Lens ²	SLC Solid Lens Cover	EPA-C Egress Adaptor Contemporary	347 347V
SLA3 SLA20		SF Single Fuse (120, 277, 347)		480 480V
SLA4 SLA20A		DF Double Fuse (208, 240, 480)		
SLA7 SLA22D				
SLA8D SLA24				
SLA9 TRA7				
SLA10 TRA8				
SLA16 TRA9				
SLA17				
Wall Mount				
WMA5 WMA17				
WMA9D WMA20				
WMA11 WMA24				
WMA12 WMA39				
WMA16				

AD5 is the 5" OD adaptor for the arm to mount on 5" OD pole

- Notes:
- 1 Wild life friendly
 - 2 Diffused Lens is available only with T3 and T5W distribution
 - 3 Consult factory for custom color, marine and corrosive finish options
 - 4 House side Shield is available only with T1, T2, T3 and T4W distributions



DIMENSIONS

See page 6 for dimensions



UCL2

ARCHITECTURAL AREA/SITE

DATE: _____ LOCATION: _____
TYPE: _____ PROJECT: _____
CATALOG #: _____

DELIVERED LUMENS

The table below shows the delivered lumens for the various lumen outputs and beam distributions. Use this chart in connection with the lumen factor (LF) capability to deliver any output required.

LED #	Drive Current	Lumen Package	Lens	Distribution	3000K 70CRI					4000K 70CRI					5000K 70CRI				
					Lumen	Bug Rating			Efficacy (Lm/W)	Lumen	Bug Rating			Efficacy (Lm/W)	Lumen	Bug Rating			Efficacy (Lm/W)
72	310	450mA Microcore Crossover	None	1	8970	1	0	1	128.4	9378	1	0	1	134.2	9755	1	0	1	139.6
				2	8440	1	0	2	120.8	8823	1	0	2	126.3	9178	2	0	2	131.4
				3	8178	1	0	2	117.1	8549	1	0	2	122.4	8893	1	0	2	127.3
				4W	8177	1	0	3	117.0	8548	1	0	3	122.4	8892	1	0	3	127.3
				1-HS	5194	0	0	0	74.3	5430	0	0	0	77.7	5648	0	0	0	80.8
				2-HS	4203	0	0	1	60.2	4394	0	0	1	62.9	4570	0	0	1	65.4
				3-HS	4033	0	0	1	57.7	4216	0	0	1	60.3	4385	0	0	1	62.8
				4W-HS	4039	0	0	1	57.8	4223	0	0	1	60.5	4393	0	0	1	62.9
				5Q	8550	3	0	1	122.4	8939	3	0	1	128.0	9298	3	0	1	133.1
				5W	8012	3	0	2	114.7	8376	3	0	2	119.9	8713	3	0	2	124.7
			Clear	1-CL	7729	1	0	1	110.6	8080	1	0	1	115.7	8405	1	0	1	120.3
				2-CL	7272	1	0	1	104.1	7602	1	0	2	108.8	7908	1	0	2	113.2
				3-CL	7046	1	0	2	100.9	7366	1	0	2	105.4	7662	1	0	2	109.7
				4W-CL	7045	1	0	3	100.8	7365	1	0	3	105.4	7661	1	0	3	109.7
				1-CL-HS	4475	0	0	0	64.1	4678	0	0	0	67.0	4866	0	0	0	69.7
				2-CL-HS	3621	0	0	1	51.8	3786	0	0	1	54.2	3938	0	0	1	56.4
				3-CL-HS	3474	0	0	1	49.7	3632	0	0	1	52.0	3778	0	0	1	54.1
				4W-CL-HS	3480	0	0	1	49.8	3639	0	0	1	52.1	3785	0	0	1	54.2
				5Q-CL	7367	2	0	1	105.5	7702	3	0	1	110.2	8011	3	0	1	114.7
				5W-CL	6903	3	0	1	98.8	7217	3	0	1	103.3	7507	3	0	1	107.5
	Diffused	3-DL	5322	1	0	1	76.2	5564	1	0	1	79.6	5788	1	0	1	82.8		
		5W-DL	5214	2	0	1	74.6	5451	2	0	1	78.0	5670	2	0	1	81.2		
	335	10000	None	1	9606	1	0	1	126.8	10042	1	0	1	132.6	10446	1	0	1	137.3
				2	9037	1	0	2	119.3	9448	2	0	2	124.7	9828	2	0	2	129.0
				3	8757	1	0	2	115.9	9155	1	0	2	120.8	9523	1	0	2	125.3
				4W	8756	1	0	3	115.6	9154	1	0	3	120.8	9522	1	0	3	125.4
				1-HS	5562	0	0	0	73.4	5814	0	0	0	76.8	6048	0	0	0	80.0
				2-HS	4500	0	0	1	59.4	4705	0	0	1	62.1	4894	0	0	1	64.9
				3-HS	4318	0	0	1	57.0	4515	0	0	1	59.6	4696	0	0	1	62.3
				4W-HS	4326	0	0	1	57.1	4522	0	0	1	59.7	4704	0	0	1	62.3
				5Q	9156	3	0	1	120.9	9572	3	0	1	126.4	9957	3	0	1	131.5
				5W	8580	3	0	2	113.3	8969	3	0	2	118.4	9330	3	0	2	123.1
			Clear	1-CL	8276	1	0	1	109.5	8652	1	0	1	114.5	9000	1	0	1	119.1
				2-CL	7787	1	0	2	103.1	8141	1	0	2	107.7	8468	1	0	2	112.1
				3-CL	7545	1	0	2	99.9	7888	1	0	2	104.4	8205	1	0	2	108.6
				4W-CL	7544	1	0	3	99.8	7887	1	0	3	104.4	8204	1	0	3	108.6
				1-CL-HS	4792	0	0	0	63.4	5010	0	0	0	66.3	5211	0	0	0	69.0
				2-CL-HS	3877	0	0	1	51.3	4054	0	0	1	53.6	4217	0	0	1	55.8
				3-CL-HS	3721	0	0	1	49.2	3890	0	0	1	51.5	4046	0	0	1	53.5
				4W-CL-HS	3727	0	0	1	49.3	3896	0	0	1	51.6	4053	0	0	1	53.6
				5Q-CL	7889	3	0	1	104.4	8247	3	0	1	109.2	8579	3	0	1	113.5
				5W-CL	7392	3	0	1	97.8	7728	3	0	1	102.3	8039	3	0	2	106.4
			Diffused	3-DL	5992	1	0	1	79.2	6264	1	0	1	82.8	6516	1	0	1	86.4
				5W-DL	5297	2	0	1	70.0	5537	2	0	1	73.1	5760	2	0	1	73.6

Submitted by Convergence North



Job Name:

LaVista Gateway Coridor UCL2

Catalog Number:

UCL2-SR-FLR-72L-310-4K7-4W-CL-DBS-SLC-SLA17-AD5-UNV

Type:

S1

Notes:

CNE23-58804



UCL2

ARCHITECTURAL AREA/SITE

DATE:

LOCATION:

TYPE:

PROJECT:

CATALOG #:

DELIVERED LUMENS (CONTINUED)

The table below shows the delivered lumens for the various lumen outputs and beam distributions. Use this chart in connection with the lumen factor (LF) capability to deliver any output required.

LED #	Drive Current	Lumen Package	Lens	Distribution	3000K 70CRI				4000K 70CRI				5000K 70CRI						
					Lumen	Bug Rating			Efficacy (Lm/W)	Lumen	Bug Rating			Efficacy (Lm/W)	Lumen	Bug Rating			Efficacy (Lm/W)
72	480	700mA Microcore Crossover	None	1	13144	1	0	1	118.8	13742	1	0	1	124.2	14294	2	0	1	129.2
				2	12367	2	0	2	111.7	12929	2	0	2	116.8	13448	2	0	2	121.5
				3	11983	2	0	2	108.3	12527	2	0	3	113.2	13031	2	0	3	117.7
				4W	11982	2	0	3	108.3	12526	2	0	3	113.2	13030	2	0	3	117.7
				1-HS	7610	0	0	0	68.8	7956	0	0	0	71.9	8276	0	0	0	74.8
				2-HS	6158	0	0	1	55.6	6438	0	0	1	58.2	6697	0	0	1	60.5
				3-HS	5909	0	0	1	53.4	6178	0	0	2	55.8	6426	0	0	2	58.1
				4W-HS	5919	1	0	2	53.5	6188	1	0	2	55.9	6437	1	0	2	58.2
				5Q	12529	3	0	1	113.2	13098	3	0	1	118.4	13625	3	0	1	123.1
				5W	11740	4	0	2	106.1	12274	4	0	2	110.9	12767	4	0	2	115.4
			Clear	1-CL	11325	1	0	1	102.3	11840	1	0	1	107.0	12316	1	0	1	111.3
				2-CL	10655	2	0	2	96.3	11139	2	0	2	100.7	11587	2	0	2	104.7
				3-CL	10324	2	0	2	93.3	10794	2	0	2	97.5	11227	2	0	2	101.5
				4W-CL	10323	1	0	3	93.3	10792	1	0	3	97.5	11226	1	0	3	101.4
				1-CL-HS	6557	0	0	0	59.2	6855	0	0	0	61.9	7131	0	0	0	64.4
				2-CL-HS	5306	0	0	1	47.9	5547	0	0	1	50.1	5770	0	0	1	52.1
				3-CL-HS	5091	0	0	1	46.0	5323	0	0	1	48.1	5537	0	0	1	50.0
				4W-CL-HS	5100	0	0	1	46.1	5332	1	0	1	48.2	5546	1	0	2	50.1
				5Q-CL	10795	3	0	1	97.5	11286	3	0	1	102.0	11739	3	0	1	106.1
				5W-CL	10115	3	0	2	91.4	10575	3	0	2	95.6	11000	4	0	2	99.4
			Diffused	3-DL	7798	2	0	1	70.4	8153	2	0	2	73.6	8481	2	0	2	76.6
				5W-DL	7640	2	0	1	69.0	7988	3	0	1	72.2	8309	3	0	1	75.1
	500	14000	None	1	13600	1	0	1	117.7	14218	2	0	1	123.0	14790	2	0	1	128.0
				2	12796	2	0	2	110.7	13377	2	0	2	115.7	13915	2	0	2	120.4
				3	12398	2	0	3	107.3	12962	2	0	3	112.2	13483	2	0	3	116.7
				4W	12397	2	0	3	107.3	12961	2	0	3	112.1	13482	2	0	3	116.7
				1-HS	7874	0	0	0	68.1	8232	0	0	0	71.2	8563	0	0	0	74.1
				2-HS	6372	0	0	1	55.1	6661	0	0	1	57.6	6929	0	0	1	60.0
				3-HS	6114	0	0	1	52.9	6392	0	0	2	55.3	6649	0	0	2	57.5
				4W-HS	6124	1	0	2	53.0	6403	1	0	2	55.4	6660	1	0	2	57.6
				5Q	12964	3	0	1	112.2	13553	3	0	1	117.3	14097	3	0	2	122.0
				5W	12147	4	0	2	105.1	12699	4	0	2	109.9	13210	4	0	2	114.3
			Clear	1-CL	11718	1	0	1	101.4	12250	1	0	1	106.0	12743	1	0	1	110.3
				2-CL	11025	2	0	2	95.4	11526	2	0	2	99.7	11989	2	0	2	103.7
				3-CL	10682	2	0	2	92.4	11168	2	0	2	96.6	11617	2	0	2	100.5
				4W-CL	10681	1	0	3	92.4	11167	1	0	3	96.6	11616	2	0	3	100.5
				1-CL-HS	6784	0	0	0	58.7	7093	0	0	0	61.4	7378	0	0	0	63.8
				2-CL-HS	5490	0	0	1	47.5	5739	0	0	1	49.7	5970	0	0	1	51.7
				3-CL-HS	5268	0	0	1	45.6	5507	0	0	1	47.7	5729	0	0	1	49.6
				4W-CL-HS	5277	1	0	1	45.7	5517	1	0	2	47.7	5738	1	0	2	49.7
				5Q-CL	11169	3	0	1	96.6	11677	3	0	1	101.0	12146	3	0	1	105.1
				5W-CL	10466	3	0	2	90.6	10942	4	0	2	94.7	11381	4	0	2	98.5
			Diffused	3-DL	8069	2	0	2	69.8	8436	2	0	2	73.0	8775	2	0	2	75.9
				5W-DL	7905	3	0	1	68.4	8265	3	0	1	71.5	8597	3	0	1	74.4

Current

currentlighting.com/aal

Page 4 of 13

Rev 03/16/23

aal_ucl2led_spec_R02



UCL2


ARCHITECTURAL AREA/SITE

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

DELIVERED LUMENS (CONTINUED)

The table below shows the delivered lumens for the various lumen outputs and beam distributions. Use this chart in connection with the lumen factor (LF) capability to deliver any output required.

LED #	Drive Current	Lumen Package	Lens	Distribution	3000K 70CRI					4000K 70CRI					5000K 70CRI				
					Lumen	Bug Rating			Efficacy (Lm/W)	Lumen	Bug Rating			Efficacy (Lm/W)	Lumen	Bug Rating			Efficacy (Lm/W)
72	700	19000	None	1	17947	2	0	1	111.9	18762	2	0	1	117.0	19516	2	0	1	121.7
				2	16885	2	0	2	105.3	17652	2	0	2	110.1	18362	3	0	3	114.5
				3	16361	2	0	3	102.0	17104	2	0	3	106.6	17792	2	0	3	110.9
				4W	16359	2	0	4	102.0	17103	2	0	4	106.6	17790	2	0	4	110.9
				1-HS	10391	0	0	0	64.8	10863	1	0	0	67.7	11300	1	0	1	70.4
				2-HS	8408	1	0	1	52.4	8790	1	0	1	54.8	9144	1	0	1	57.0
				3-HS	8068	1	0	2	50.3	8435	1	0	2	52.6	8774	1	0	2	54.7
				4W-HS	8082	1	0	2	50.4	8449	1	0	2	52.7	8789	1	0	2	54.8
				5Q	17106	4	0	2	106.6	17884	4	0	2	111.5	18603	4	0	2	116.0
			5W	16029	4	0	2	99.9	16758	4	0	2	104.5	17431	4	0	2	108.7	
			Clear	1-CL	15463	2	0	1	96.4	16166	2	0	1	100.8	16815	2	0	1	104.8
				2-CL	14548	2	0	2	90.7	15209	2	0	2	94.8	15821	2	0	2	98.6
				3-CL	14096	2	0	3	87.9	14737	2	0	3	91.9	15330	2	0	3	95.6
				4W-CL	14095	2	0	3	87.9	14736	2	0	3	91.9	15328	2	0	3	95.6
				1-CL-HS	8953	0	0	0	55.8	9359	0	0	0	58.4	9736	0	0	0	60.7
				2-CL-HS	7244	1	0	1	45.2	7574	1	0	1	47.2	7878	1	0	1	49.1
				3-CL-HS	6951	0	0	2	43.3	7267	1	0	2	45.3	7559	1	0	2	47.1
				4W-CL-HS	6963	1	0	2	43.4	7280	1	0	2	45.4	7572	1	0	2	47.2
				5Q-CL	14739	3	0	2	91.9	15409	4	0	2	96.1	16028	4	0	2	99.9
			Diffused	5W-CL	13811	4	0	2	86.1	14438	4	0	2	90.0	15019	4	0	2	93.6
				3-DL	10648	2	0	2	66.4	11132	2	0	2	69.4	11579	2	0	2	72.2
5W-DL	10432	3		0	2	65.0	10906	3	0	2	68.0	11344	3	0	2	70.7			





**UCL2**


ARCHITECTURAL AREA/SITE

DATE: _____ LOCATION: _____

TYPE: _____ PROJECT: _____

CATALOG #: _____

DIMENSIONS**ANGLED HOOD CONFIGURATION****BELL HOOD CONFIGURATION****FLARE HOOD CONFIGURATION****SKIRTED BELL HOOD CONFIGURATION**

**UCL2**

ARCHITECTURAL AREA/SITE

DATE: _____ LOCATION: _____

TYPE: _____ PROJECT: _____

CATALOG #: _____

PHOTOMETRY


UCL2-ANG-72L-700-4K7-1

LUMINAIRE DATA

Description	4000 Kelvin, 70CRI
Delivered Lumens	18,762
Watts	160.4
Efficacy	117.0
IES Type	I
BUG Rating	B2-U0-G1
Mounting Height	30 ft
Grid Scale	30 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	16473	88%
Downward House Side	2289	12%
Downward Total	18762	100%
Upward Street Side	0	0%
Upward House Side	0	0%
Upward Total	0	0%
Total Flux	18762	100%

ISOFOOT CANDLE PLOT


UCL2-ANG-72L-700-4K7-2

LUMINAIRE DATA

Description	4000 Kelvin, 70CRI
Delivered Lumens	17,652
Watts	160.4
Efficacy	110.0
IES Type	II
BUG Rating	B2-U0-G2
Mounting Height	30 ft
Grid Scale	30 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	14521	82%
Downward House Side	3131	18%
Downward Total	17652	100%
Upward Street Side	0	0%
Upward House Side	0	0%
Upward Total	0	0%
Total Flux	17652	100%

ISOFOOT CANDLE PLOT


UCL2-ANG-72L-700-4K7-3


LUMINAIRE DATA

Description	4000 Kelvin, 70CRI
Delivered Lumens	17105
Watts	160.4
Efficacy	106.6
IES Type	III
BUG Rating	B2-U0-G3
Mounting Height	30 ft
Grid Scale	30 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	14403	84%
Downward House Side	2702	16%
Downward Total	17105	100%
Upward Street Side	0	0%
Upward House Side	0	0%
Upward Total	0	0%
Total Flux	17105	100%

ISOFOOT CANDLE PLOT

**UCL2**

ARCHITECTURAL AREA/SITE

DATE: _____ LOCATION: _____

TYPE: _____ PROJECT: _____

CATALOG #: _____

PHOTOMETRY


UCL2-ANG-72L-700-4K7-4W

LUMINAIRE DATA

Description	4000 Kelvin, 70CRI
Delivered Lumens	17103
Watts	160.4
Efficacy	106.6
IES Type	IV Wide
BUG Rating	B2-U0-G4
Mounting Height	30 ft
Grid Scale	30 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	14997	88%
Downward House Side	2106	12%
Downward Total	17103	100%
Upward Street Side	0	0%
Upward House Side	0	0%
Upward Total	0	0%
Total Flux	17103	100%

ISOFOOT CANDLE PLOT


UCL2-ANG-72L-700-4K7-5Q

LUMINAIRE DATA

Description	4000 Kelvin, 70CRI
Delivered Lumens	17884
Watts	160.4
Efficacy	111.5
IES Type	VS
BUG Rating	B4-U0-G2
Mounting Height	30 ft
Grid Scale	30 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	8942	50%
Downward House Side	8942	50%
Downward Total	17884	100%
Upward Street Side	0	0%
Upward House Side	0	0%
Upward Total	0	0%
Total Flux	17884	100%

ISOFOOT CANDLE PLOT


UCL2-ANG-72L-700-4K7-5W

LUMINAIRE DATA

Description	4000 Kelvin, 70CRI
Delivered Lumens	16758
Watts	160.4
Efficacy	104.5
IES Type	VS
BUG Rating	B4-U0-G2
Mounting Height	30 ft
Grid Scale	30 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	8379	50%
Downward House Side	8379	50%
Downward Total	16758	100%
Upward Street Side	0	0%
Upward House Side	0	0%
Upward Total	0	0%
Total Flux	16758	100%

ISOFOOT CANDLE PLOT




UCL2

ARCHITECTURAL AREA/SITE

DATE: _____ LOCATION: _____
TYPE: _____ PROJECT: _____
CATALOG #: _____

TM-30 DATA

COLOR VECTOR GRAPHIC




— Reference Illuminant — Test Source

TEST SOURCE

MBM TEST RESULTS	
CCT (K)	3947
CIE Ra	72
Duv	0.0004
x	0.3831
y	0.3793
Rf	68
Rg	99

SPECTRAL POWER DISTRIBUTION COMPARISON



ELECTRICAL DATA

Electrical												Dimming					
Light Engine	System Current	System Watts	Line Voltage		Amps AC						Min. Power Factor	Max THD (%)	Dimming Range	Source current out of 0-10V		Absolute voltage range on 0-10V (+)	
			VAC	HZ	120	208	240	277	347	480				Min	Max	Min	Max
72	310 mA	69.9	120-480	50/60	0.58	0.34	0.29	0.25	0.20	0.15	>0.9	20	10% to 100%	0mA	1mA	0V	10V
	335 mA	75.7			0.63	0.36	0.32	0.27	0.22	0.16							
	480 mA	110.7			0.92	0.53	0.46	0.40	0.32	0.23							
	500 mA	115.6			0.96	0.56	0.48	0.42	0.33	0.24							
	700 mA	160.4			1.34	0.77	0.67	0.58	0.46	0.33							

TM-21 LIFETIME CALCULATION - PROJECTED LUMEN MAINTENANCE (25°C / 77°F)						
HOURS	0	25,000	36,000	50,000	100,000	REPORTED L70
Projected Lumen Maintenance	100%	98.0%	96.9%	95.5%	90.7%	> 60,000

AMBER MULTIPLIER	
CCT	MULTIPLIER
5000K	1
AM	0.1727

2700K MULTIPLIER	
CCT	MULTIPLIER
5000K	1
2700K	0.897

LENS OPTION MULTIPLIER	
CLEAR LENS	DIFFUSED LENS
0.8615	0.7098

ADDITIONAL INFORMATION

PHOTOCELL / EGRESS ADAPTERS

- Adapter(s) shall slip over a 4"/100mm DIA. pole with the luminaire or arm slipping over the adapter to add a total of 4.5"/114mm to the overall height. Adapter(s) shall be prewired, independently rotatable 359°, and have a cast access cover with an integral lens and lanyard.
- Photocell adapter shall include an internal twist lock receptacle. Photocell by others.
- Egress adapter shall require an auxiliary 120 volt supply for operation of an integral MR16 lamp in the event of emergency. The lamp may be aimed and locked into position with an adjustment range of 15°-45°. Adapter shall have a socket that accepts miniature bi-pin MR16 lamps up to 50 watts, lamp by others.

**UCL2**

ARCHITECTURAL AREA/SITE

DATE: _____ LOCATION: _____

TYPE: _____ PROJECT: _____


CATALOG #: _____

ADDITIONAL INFORMATION CONTINUED**MOUNTING POLE OPTIONS**

SLA2-D

WT: 6 LBS

EPA: .30




4" POLE

SLA3

WT: 8 LBS

EPA: .77




4" POLE

SLA4

WT: 14 LBS

EPA: 1.39




4" POLE

SLA7

WT: 9 LBS

EPA: 1.34




4" POLE

SLA8D

WT: 5 LBS

EPA: .40




4" OR 5" POLE

SLA9

WT: 18 LBS

EPA: 1.90




4" POLE

SLA10

WT: 9 LBS

EPA: 1.09




4" POLE

SLA16

WT: 18 LBS

EPA: 2.88



4" POLE

**UCL2**

ARCHITECTURAL AREA/SITE

DATE: _____ LOCATION: _____

TYPE: _____ PROJECT: _____


CATALOG #: _____

ADDITIONAL INFORMATION CONTINUED**MOUNTING POLE OPTIONS**

SLA17

WT: 18 LBS

EPA: 1.50




4" POLE

SLA18

WT: 12 LBS

EPA: .85




4" POLE

SLA20

WT: 10 LBS

EPA: .70




4" POLE

SLA20A

WT: 15 LBS

EPA: 1.30




4" POLE

SLA22D

WT: 4 LBS

EPA: .44




4" POLE

SLA24

WT: 9 LBS

EPA: .85




4" POLE

TRA7

WT: 12 LBS

EPA: .90




4" POLE

TRA8

WT: 13 LBS

EPA: 1.34



4" POLE

**UCL2**

ARCHITECTURAL AREA/SITE

DATE: _____ LOCATION: _____

TYPE: _____ PROJECT: _____


CATALOG #: _____

ADDITIONAL INFORMATION CONTINUED**MOUNTING POLE OPTIONS**

TRA9

WT: 17 LBS

EPA: 1.90




4" POLE

MOUNTING WALL OPTIONS


WMA5

WT: 6 LBS




WMA9D

WT: 6 LBS




WMA11

WT: 10 LBS




WMA12

WT: 12 LBS




WMA16

WT: 22 LBS



WMA17

WT: 15 LBS



**UCL2**

ARCHITECTURAL AREA/SITE

DATE: _____ LOCATION: _____


TYPE: _____ PROJECT: _____

CATALOG #: _____

ADDITIONAL INFORMATION CONTINUED**MOUNTING WALL OPTIONS**


WMA20

WT: 12 LBS





WMA24

WT: 12 LBS



WMA39


WT: 14 LBS

**OPTIONAL MOUNTING**

* Catenary Mount

* Pendant Mount

* Contact factory for more information



A Mtg. Hgt.	B Wall Thickness	C Butt Diameter	TOTAL LUM. WEIGHT	MAXIMUM EPA					OLD CAT. NUMBER	CATALOG NUMBER
				90	100	110	120	130		
20	0.188"	5	95	7.2	5.0	4.6	3.7	3.0	78S-034	RSA20D5-4-**

C BUTT DIA.	D TOP DIA.	F BOLT CIR. DIA.	G BASE SQ.	H BOLT PROJ.	I BOLT SIZE
5	5	7.5 - 8	7.5	2	.75 x 17 x 3

Dimensions in Inches

CUSTOMER NAME:	
PROJECT:	LOCATION:
NOTES:	QUANTITY:

RSA20D5-4
FINISH

CATALOG NUMBER

Pole

The pole shaft will be constructed of seamless extruded tube of 6063 Aluminum Alloy per the requirements of ASTM B221. The shaft assembly shall be full-length heat treated after base weld to produce a T6 temper.

Base Style

4-Bolt Cast Aluminum Base Flange of Alloy 356-T6 with Aluminum Bolt Covers (Alloy 356-F) and Stainless Steel Hex Head Attaching Screws.




Handhole

2" x 4" Handhole with curved Lap Style Aluminum Door and two (2) SS Self-Tapping Attaching Screws. A Grounding Provision incorporating a tapped 1/4"-20NC hole is provided opposite the Handhole.

Anchorage

Anchorage Kit will include four (4) L-shaped Steel Anchor Bolts conforming to AASHTO M314-90 Grade 55. Ten inches (10") of threaded end will be galvanized per ASTM A153. Kits will contain four (4) Hex Nuts, four (4) Lock Washers, and four (4) Flat Washers (all components Galvanized Steel). A bolt circle template will be provided.




Vibration Damper

When determined necessary by Hapco, a Vibration Damper will be factory-installed inside the pole shaft. Customer specification of the damper is available.

Mounting Designation

Side Drill Mount - For Side Drill Mount applications specify luminaire type, quantity and orientation. A luminaire drilling template must be supplied at time of order.



Tenon Mount
For Tenon Mount applications specify both Tenon diameter (2.375", 2.875", 3.5", etc.) and length (3", 4", etc.).



EPA Notes: Effective Projected Area (EPA) in square feet. EPA's calculated using wind velocity (mph) indicated in accordance with 2009 AASHTO LTS-5 using a 25 year design life. Maximum EPA is based on the luminaire weight shown. Increased luminaire weight may reduce the maximum EPA. If weight is exceeded, or if other design life or code is required, please consult the factory.

 26252 Hillman Highway
Abingdon, VA 24210
800.368.7171
www.hapco.com



UCL2

ARCHITECTURAL AREA/SITE

DATE: _____ LOCATION: _____
TYPE: _____ PROJECT: _____
CATALOG #: _____

ORDERING GUIDE

Example: UCL2-WND-BLU-FLR-36L-420-4K7-2-CL-BL-WIRSC-SLA2-D-UNV

CATALOG # _____

HOUSING

UCL2					
Housing	LED Quantity	Lumen Output	CCT/CRI	Distribution	Finish
UCL2 Universe Large 2.0	72L 72 LED	310 450mA Microcore Crossover	AMB Amber-595nm Peak ¹	1 Type I	BLS Black Gloss Smooth
Optional Element		335 335mA, 10000 Lumens	3K7 3000K, 70 CRI	2 Type II	BLT Black Matte Textured
WND Universe Medium with Luminous Window		480 700mA Microcore Crossover	4K7 4000K, 70 CRI	3 Type III	DBS Dark Bronze Gloss Smooth
SR Universe Medium with Luminous Solid Rings		500 500mA, 14000 Lumens	5K7 5000K, 70 CRI	4W Type IV Wide	DBT Dark Bronze Matte Textured
VSL Universe Medium with Luminous Vertical Slots		700 700mA, 19000 Lumens		5Q Type V Square	GTT Graphite Matte Textured
LUM Universe Medium with Luminous Rings				5W Type V Wide	LGS Light Grey Gloss Smooth
Optional Internal Lens					LGT Light Grey Matte Textured
BLU Blue					PSS Platinum Silver Gloss Smooth
RD Red					VGT Verde Green Matte Textured
GRN Green					WHS White Gloss Smooth
Hood Style					WHT White Matte Textured
ANG Angled Hood					Color Option
BEL Bell Hood					CC ³ Custom Color
FLR Flared Hood					
SKB Skirted Bell Hood					

Mounting	Optional Lens	Options	Mounting Options	Voltage
Pole Mount	CL Clear Lens	HS House Side Shield ⁴	PCA-C Photocontrol Adaptor Contemporary	UNV 120-277V
SLA2-D SLA18	DL Diffused Lens ²	SLC Solid Lens Cover	EPA-C Egress Adaptor Contemporary	347 347V
SLA3 SLA20		SF Single Fuse (120, 277, 347)		480 480V
SLA4 SLA20A		DF Double Fuse (208, 240, 480)		
SLA7 SLA22D				
SLA8D SLA24				
SLA9 TRA7				
SLA10 TRA8				
SLA16 TRA9				
SLA17				
Wall Mount				
WMA5 WMA17				
WMA9D WMA20				
WMA11 WMA24				
WMA12 WMA39				
WMA16				


2-AD5 is the 5" OD adaptor for the arm to mount on 5" OD pole

Notes:

- 1 Wild life friendly
- 2 Diffused Lens is available only with T3 and T5W distribution
- 3 Consult factory for custom color, marine and corrosive finish options
- 4 House side Shield is available only with T1, T2, T3 and T4W distributions

DIMENSIONS

See page 6 for dimensions





Job Name:
LaVista Gateway Corridor UCL2

Catalog Number:
RSA20D5-4-P496-ABT-BC


Notes:

Type:

S2 POLE

CNE23-58804

RSA Round Straight Aluminum Pole No Arm — 4-Bolt Base



WARNING:
Do not install light pole without luminaire.

Satin Aluminum or Powder Coated
Finish per Customer Specification.

A Mtg. Hgt.	B Wall Thickness	C Butt Diameter	TOTAL LUM. WEIGHT	MAXIMUM EPA					OLD CAT. NUMBER	CATALOG NUMBER
				90	100	110	120	130		
20	0.188"	5	95	7.2	5.0	4.6	3.7	3.0	78S-034	RSA20D5-4-**-

C BUTT DIA.	D TOP DIA.	F BOLT CIR. DIA.	G BASE SQ.	H BOLT PROJ.	I BOLT SIZE
5	5	7.5 - 8	7.5	2	.75 x 17 x 3

Dimensions in Inches

CUSTOMER NAME:	
PROJECT:	LOCATION:
NOTES:	QUANTITY:

RSA20D5-4

CATALOG NUMBER

FINISH

Pole

The pole shaft will be constructed of seamless extruded tube of 6063 Aluminum Alloy per the requirements of ASTM B221. The shaft assembly shall be full-length heat treated after base weld to produce a T6 temper.

Base Style

4-Bolt Cast Aluminum Base Flange of Alloy 356-T6 with Aluminum Bolt Covers (Alloy 356-F) and Stainless Steel Hex Head Attaching Screws.




Handhole

2" x 4" Handhole with curved Lap Style Aluminum Door and two (2) SS Self-Tapping Attaching Screws. A Grounding Provision incorporating a tapped 1/4"-20NC hole is provided opposite the Handhole.

Anchorage

Anchorage Kit will include four (4) L-shaped Steel Anchor Bolts conforming to AASHTO M314-90 Grade 55. Ten inches (10") of threaded end will be galvanized per ASTM A153. Kits will contain four (4) Hex Nuts, four (4) Lock Washers, and four (4) Flat Washers (all components Galvanized Steel). A bolt circle template will be provided.




Vibration Damper

When determined necessary by Hapco, a Vibration Damper will be factory-installed inside the pole shaft. Customer specification of the damper is available.

Mounting Designation

Side Drill Mount - For Side Drill Mount applications specify luminaire type, quantity and orientation. A luminaire drilling template must be supplied at time of order.



Tenon Mount

For Tenon Mount applications specify both Tenon diameter (2.375", 2.875", 3.5", etc.) and length (3", 4", etc.).



EPA Notes: Effective Projected Area (EPA) in square feet. EPA's calculated using wind velocity (mph) indicated in accordance with 2009 AASHTO LTS-5 using a 25 year design life. Maximum EPA is based on the luminaire weight shown. Increased luminaire weight may reduce the maximum EPA. If weight is exceeded, or if other design life or code is required, please consult the factory.



26252 Hillman Highway
Abingdon, VA 24210
800.368.7171
www.hapco.com