

CITY OF LA VISTA
MAYOR AND CITY COUNCIL REPORT
SEPTEMBER 6, 2016 AGENDA

Subject:	Type:	Submitted By:
ZONING TEXT AMENDMENTS — VARIOUS AMENDMENTS TO ADDRESS ADA PARKING	◆ RESOLUTION ORDINANCE RECEIVE/FILE	ANN BIRCH COMMUNITY DEVELOPMENT DIRECTOR

SYNOPSIS

A public hearing has been scheduled and an ordinance prepared to amend Section 7.08 (Off-Street Parking: Parking for Individuals with Disabilities) to the Zoning Ordinance.

FISCAL IMPACT

N/A.

RECOMMENDATION

Approval.

BACKGROUND

Upon staff review of Section 7.08 (Off-Street Parking: Parking for Individuals with Disabilities), it was concluded an update to the regulations was warranted. The proposed changes add a separate column for the required Minimum Number of Van-Accessible Parking Spaces within the table in Section 7.08.01. Additional minor changes are proposed to increase the number of accessible spaces that shall be served by an access aisle.

Redline copies of the aforementioned sections are attached.

STAFF RECOMMENDATION:

Staff recommends approval of the proposed amendments.

ORDINANCE NO. _____

AN ORDINANCE TO AMEND SECTION 7.08 OF ORDINANCE NO. 848 (ZONING ORDINANCE); TO REPEAL SECTION 7.08 OF ORDINANCE NO. 848 AS PREVIOUSLY ENACTED; TO PROVIDE FOR SEVERABILITY; AND TO PROVIDE FOR THE EFFECTIVE DATE HEREOF.

BE IT ORDAINED BY THE MAYOR AND CITY COUNCIL OF THE CITY OF LA VISTA, SARPY COUNTY, NEBRASKA:

SECTION 1. Amendment of Section 7.08. Section 7.08 of the Ordinance No. 848 is hereby amended to read as follows:

Section 7.08 Off-Street Parking: Parking for Individuals with Disabilities

7.08.01 In conformance with the Americans with Disabilities Act (ADA) and the Nebraska Accessibility Guidelines, if parking spaces are provided for self-parking by employees or visitors, or both, then accessible spaces shall be provided in each parking area in conformance with the table in this section. Spaces required by the table need not be provided in the particular lot. They may be provided in a different, if equivalent or greater accessibility, in terms of distance from an accessible entrance, cost and convenience, is ensured.

Total Parking Spaces	Column A Required Minimum Number of Accessible Spaces	Column B Minimum Number of Van- Accessible Parking Spaces (1 of 6 available spaces)
1 to 25	1	1
26 to 50	2	1
51 to 75	3	1
76 to 100	4	1
101 to 150	5	1
151 to 200	6	1
201 to 300	7	2
301 to 400	8	2
401 to 500	9	2
501 to 1,000	2 percent of the total	1/6 of Column A
1,001 and over	20 plus 1 for each 100 over 1,000	1/6 of Column A

7.08.02 Except as provided *in* Section 7.08.02.01 of this Ordinance, access aisles adjacent to accessible spaces shall be sixty (60) inches (1525 mm) wide minimum. (*Ordinance No. 899, 2-04-03*)

7.08.02.01 One (1) in every eight (6) accessible spaces, but not less than one, shall be served by an access aisle ninety-six (96) inches (2440 mm) wide minimum and shall be designated "van accessible" as required by Section 7.08.04 of this Ordinance. The vertical clearance at such spaces shall comply with 7.08.05 of this Ordinance. All such spaces may be grouped on one (1) level of a parking structure.

Parking access aisles shall be part of an accessible route to the building or facility entrance. Two (2) accessible parking spaces may share a common access aisle.

Parked vehicle overhangs shall not reduce the clear width of an accessible route. Parking spaces and access aisles shall be level with slopes not exceeding 1:50 (2%) in all directions, except for angled parking spaces which must have access aisles located on the passenger side of the parking spaces.

7.08.02.02 If passenger-loading zones are provided, then at least one (1) passenger loading zone shall comply with 7.08.06 of this Ordinance.

7.08.02.03 At facilities providing medical care and other services for persons with mobility impairments, parking spaces complying with 7.08 of this Ordinance shall be provided in accordance with 7.08.01 of this Ordinance; except as follows:

1. Outpatient units and facilities: ten percent (10%) of total number of parking spaces provided serving each such outpatient unit or facility;
2. Units and facilities that specialize in treatment or services for persons with mobility impairments: twenty percent (20%) of the total number of parking spaces provided serving each such unit or facility.

7.08.02.04 Valet parking: valet parking facilities shall provide a passenger loading zone complying with 7.08.06 of this Ordinance located on an accessible route to the entrance of the facility. Sections 7.08.01, 7.08.02.01, and 7.08.02.03 of this Ordinance do not apply to valet parking.

7.08.03 Location of accessible parking spaces serving a particular building shall be located on the shortest accessible route of travel from adjacent parking to an accessible entrance.

7.08.03.01 In parking facilities that do not serve a particular building, accessible parking shall be located on the shortest accessible route of travel to an accessible pedestrian entrance of the parking facility.

7.08.03.02 In buildings with multiple accessible entrances with adjacent parking, accessible parking spaces shall be dispersed and located closest to the accessible entrances.

7.08.04 Signage of accessible parking spaces shall be designated as reserved by a sign showing the symbol of accessibility. Spaces complying 7.08.02.01 shall have an additional sign "Van Accessible" mounted below the symbol of accessibility. Such signs shall be located so they cannot be obscured by a vehicle parked in the space. ADA mandates the sign height be at least sixty (60) inches above ground surface measured from the bottom of the sign.

7.08.05 Minimum vertical clearance of one hundred fourteen (114) inches (2895mm) at accessible passenger loading zones and along at least one vehicle access route to such areas from site entrance(s) and exit(s). At parking spaces complying with 7.08.02.01, provide minimum vertical clearance of ninety-eight (98) inches (2490mm) at the parking space and along at least one vehicle access route to such spaces from site entrance(s) and exit(s).

7.08.06 Passenger Loading Zones shall provide an access aisle at least sixty (60) inches (1525mm) wide and twenty (20) feet (240inches) (6100mm) long adjacent and parallel to the vehicle pull-up space. If there are curbs between the access aisle and the vehicle pull-up space, then a curb ramp complying with accessibility standards shall be provided. Vehicle standing spaces and access aisles shall be level with surface slopes not exceeding 1:50 (2%) in all directions.

SECTION 4. Repeal of Section 7.08 as Previously Enacted. Section 7.08 of Ordinance No. 848 as previously enacted is hereby repealed.

SECTION 5. Severability Clause. If any section, subsection, sentence, clause or phrase of this ordinance is, for any reason, held to be unconstitutional or invalid, such unconstitutionality or invalidity shall not affect the validity of the remaining portions of this ordinance. The Mayor and City Council of the City of La Vista hereby declare that it would have passed this ordinance and each section, subsection, clause or phrase thereof, irrespective of the fact that any one or more sections, subsections, sentences, clauses or phrases be declared unconstitutional or invalid.

SECTION 6. Effective Date. This ordinance shall be in full force and effect from and after passage, approval and publication as provided by law.

SECTION 7. This ordinance shall be published in pamphlet form and take effect as provided by law.

PASSED AND APPROVED THIS 6TH DAY OF SEPTEMBER 2016.

CITY OF LA VISTA

Douglas Kindig, Mayor

ATTEST:

Pamela A. Buethe, CMC
City Clerk

I:\Community Development\Planning Department\City Council\Ordinances-Resolutions\2016\Amend Zoning Ordinance 7.08.Docx

Section 7.08 Off-Street Parking: Parking for Individuals with Disabilities

7.08.01 In conformance with the Americans with Disabilities Act (ADA) and the Nebraska Accessibility Guidelines, if parking spaces are provided for self-parking by employees or visitors, or both, then accessible spaces shall be provided in each parking area in conformance with the table in this section. Spaces required by the table need not be provided in the particular lot. They may be provided in a different, if equivalent or greater accessibility, in terms of distance from an accessible entrance, cost and convenience, is ensured.

Total Parking Spaces	Column A Required Minimum Number of Accessible Spaces	Column B Minimum Number of Van- Accessible Parking Spaces (1 of six 6 available spaces)
1 to 25	1	1
26 to 50	2	1
51 to 75	3	1
76 to 100	4	1
101 to 150	5	1
151 to 200	6	1
201 to 300	7	2
301 to 400	8	2
401 to 500	9	2
501 to 1,000	2 percent of the total	1/6 of Column A
1,001 and over	20 plus 1 for each 100 over 1,000	1/6 of Column A

7.08.02 Except as provided *in* Section 7.08.02.01 of this Ordinance, access aisles adjacent to accessible spaces shall be sixty (60) inches (1525 mm) wide minimum. (*Ordinance No. 899, 2-04-03*)

7.08.02.01 One (1) in every eight ~~(6)~~(8) accessible spaces, but not less than one, shall be served by an access aisle ninety-six (96) inches (2440 mm) wide minimum and shall be designated "van accessible" as required by Section 7.08.04 of this Ordinance. The vertical clearance at such spaces shall comply with 7.08.05 of this Ordinance. All such spaces may be grouped on one (1) level of a parking structure.

Parking access aisles shall be part of an accessible route to the building or facility entrance. Two (2) accessible parking spaces may share a common access aisle.

Parked vehicle overhangs shall not reduce the clear width of an accessible route. Parking spaces and access aisles shall be level with slopes not exceeding 1:50 (2%) in all directions. Except, except for angled parking spaces which must have access aisles located on the passenger side of the parking spaces.

7.08.02.02 If passenger-loading zones are provided, then at least one (1) passenger loading zone shall comply with 7.08.06 of this Ordinance.

7.08.02.03 At facilities providing medical care and other services for persons with mobility impairments, parking spaces complying with 7.08 of this Ordinance shall be provided in accordance with 7.08.01 of this Ordinance; except as follows:

1. Outpatient units and facilities: ten percent (10%) of total number of parking spaces provided serving each such outpatient unit or facility;
2. Units and facilities that specialize in treatment or services for persons with mobility impairments: twenty percent (20%) of the total number of parking spaces provided serving each such unit or facility.

7.08.02.04 Valet parking: valet parking facilities shall provide a passenger loading zone complying with 7.08.06 of this Ordinance located on an accessible route to the entrance of the facility. Sections 7.08.01, 7.08.02.01, and 7.08.02.03 of this Ordinance do not apply to valet parking.

7.08.03 Location of accessible parking spaces serving a particular building shall be located on the shortest accessible route of travel from adjacent parking to an accessible entrance.

7.08.03.01 In parking facilities that do not serve a particular building, accessible parking shall be located on the shortest accessible route of travel to an accessible pedestrian entrance of the parking facility.

7.08.03.02 In buildings with multiple accessible entrances with adjacent parking, accessible parking spaces shall be dispersed and located closest to the accessible entrances.

7.08.04 Signage of accessible parking spaces shall be designated as reserved by a sign showing the symbol of accessibility. Spaces complying 7.08.02.01 shall have an additional sign- "Van Accessible" mounted below the symbol of accessibility. Such signs shall be located so they cannot be obscured by a vehicle parked in the space. ADA mandates the sign height be at least sixty (60) inches above ground surface measured from the bottom of the sign.

7.08.05 Minimum vertical clearance of one hundred fourteen (114) inches (2895mm) at accessible passenger loading zones and along at least one vehicle access route to such areas from site entrance(s) and exit(s). At parking spaces complying with 7.08.02.01, provide minimum vertical clearance of ninety-eight (98) inches (2490mm) at the parking space and along at least one vehicle access route to such spaces from site entrance(s) and exit(s).

7.08.06 Passenger Loading Zones shall provide an access aisle at least sixty (60) inches (1525mm) wide and twenty (20) feet (240inches) (6100mm) long adjacent and parallel to the vehicle pull-up space. If there are curbs between the access aisle and the vehicle pull-up space, then a curb ramp complying with accessibility standards shall be provided. Vehicle standing spaces and access aisles shall be level with surface slopes not exceeding 1:50 (2%) in all directions.